

- Up to 4.2 GPM
- Up to 3000 PSI
- Stainless Steel or Mild Steel Cabinet
- Accepts Hot Water Up to 185°F



- Industrial-Grade Motor is connected to the rugged, class-leading, tri-plunger, oil-bath LT (stainless steel model) or LM (mild steel model) High-Pressure Pump (with 7-year warranty) by dual, V-cogged belts. Pulleys are made of cast iron and can be easily adjusted by turning two bolts.
- Quick-couple Nozzles are made of hardened stainless steel and color-coded for easy selection of spray pattern: 15°, 25°, 40°.
- Heavy-duty **Cabinet** rides on four **Rubber Feet** for absorption of vibration.
- Hour Meter is standard on the Mild Steel versions only.
- Inlet Filter strainer protects pump from debris.
- Easily handles Water Up To 185°.

 50 ft. of double steel-wire braid High Pressure Hose with 24-inch Hose Guard for burst protection and swivel crimp fitting for tangle-free handling of hose and trigger gun.

SEA3-11024D

with mild steel cabine

- Add portability to the SEA with optional Wheel Kit (stainless steel model #8.904-527.0 or mild steel model #9.801-031.0), including detergent jug holder. Optional Hose Reel (#8.903-521.0) provides tanglefree handling of up to 100 ft. of highpressure hose.
- Easy-to-attach Detergent Injector for easy application of soap.
- Helpful Tri-Lingual Labels with operating instructions in English, Spanish and French for added liability protection and operator convenience.
- Compact Design, 31" L x 21" W x 16" H.

 Many Safety Features, including a thermal pump protector to prevent the buildup of excessive pressures or heat.

SEA3-11024D

Shown with stainless steel cabinet

- Time-Delay Shutdown (stainless steel model only) automatically turns off unit, if not in use for a set time, for protection against unattended operation.
- With the switch in the 'ON' position, the optional Auto Start/Stop function allows the unit to be turned on with the pull of the trigger for convenient remote operation. (This option replaces Time-Delay Shutdown.)
- Optional rust-free Float Tank with stainless steel inlet filter and backflow protection (stainless steel model only and cannot be ordered with wheel kit option).
- 36 ft. of high-grade Electrical Cord with Ground Fault Circuit Interrupter (on single-phase models) for operator safety.

#LANDATOUGH Pressure Washers Built to Last - <u>landa.com</u>



## WHY CHOOSE THE SEA?

This top-of-the-line stationary cold-water series features a heavy-duty stainless steel or mild steel cabinet and comes standard with an insulated variable pressure wand, 50' of hose, and time delay shutdown. Available options include our LanCom wireless remote control, floor stand, and wall mount bracket assembly. There is even an optional wheel kit for adding mobility, making an already top-quality machine even more flexible than before. This unit is ideal for cleaning a variety of indoor surfaces, and can be plumbed for plug-and-wash outdoor applications as well.



Model #	Part #	Cabinet	GPM	PSI	Pump RPM	Pump	Motor HP	Volts	Phase	Amps	Ship Wt (lbs)
SEA3-11024D	1.106-500.0	Stainless Steel	2.8	1000	1540	LB3030R	2.0	120	1	20	210
SEA4-20024A	1.106-501.0	Stainless Steel	4.2	2000	1013	LT6036R.2	6.2	230	1	28	280
SEA4-20024B	1.106-502.0	Stainless Steel	4.2	2000	1013	LT6036R.2	6.2	230	3	16	220
SEA4-20024C	1.106-503.0	Stainless Steel	4.2	2000	1013	LT6036R.2	6.2	460	3	7.2	220
SEA4-20024G	1.106-505.0	Stainless Steel	4.2	2000	997	LT6036R.2	6.2	208	1	30	297
SEA4-20024H	1.106-506.0	Stainless Steel	4.2	2000	1028	LT6036R.2	6.2	208	3	18.5	220
SEA4-30024B	1.106-507.0	Stainless Steel	3.5	3000	943	LT6036R.2	7.5	230	3	21.5	235
SEA4-30024C	1.106-508.0	Stainless Steel	3.5	3000	943	LT6036R.2	7.5	460	3	10.5	305
SEA3-11024D	1.106-583.0	Mild Steel	2.8	1000	1500	LB3030R	2.0	120	1	20	275
SEA4-20024A	1.106-584.0	Mild Steel	4.2	2000	1281	LM4035R.3	6.2	230	1	29	275
SEA4-20024B	1.106-585.0	Mild Steel	4.2	2000	1281	LM4035R.3	6.2	230	3	11	275
SEA4-20024C	1.106-586.0	Mild Steel	4.2	2000	1281	LM4035R.3	6.2	460	3	11	275
SEA4-20024H	1.106-587.0	Mild Steel	4.2	2000	1281	LM4035R.3	6.2	208	3	16	275
SEA4-30024B	1.106-588.0	Mild Steel	3.5	3000	1070	LM4035R.3	7.5	230	3	19	275
SEA4-30024C	1.106-589.0	Mild Steel	3.5	3000	1070	LM4035R.3	7.5	460	3	11	275

Dimensions: 31"L x 21"W x 16"H

Field Install	ed Options & Accessories	Mild Steel N	lodels Only	Stainless Steel Models Only			
9.801-036.0	Cox Hose Reel Kit (floor stand / wall mount)	8.903-045.0	Time Delay Shutdown Kit 120v 1ph •	8.929-497.0	LanCom Kit 1-step 460V 3 ph + ∘ •		
8.903-521.0	E-Zee Hose Reel & Mounting Kit (fits wheel kit)	8.929-374.0	Time Delay Shutdown Kit 208/230v 1ph •	8.929-498.0	LanCom Kit 2-step 460V 3 ph • • •		
9.802-265.0	Hose Reel, Mini, (fits wall bracket, 150' capacity)	8.903-041.0	Time Delay Shutdown Kit 3ph •	8.930-163.0	LanCom Kit 1-step 208/230V 3ph • • •		
8.711-860.0	Hose Reel, Mini, (fits wall bracket, 100' capacity)	8.929-376.0	Auto start/Stop Kit 120v 1ph •	8.930-177.0	LanCom Kit 2 step 208/230V 3ph •••		
9.801-035.0	Wheel Kit (4 casters) for Floor Stands	8.929-377.0	Auto Start/Stop Kit 208/230v 1ph •	8.929-382.0	LanCom Kit 1-step 208/230v 1 ph • • •		
9.801-031.0	Wheel Kit with Detergent Rack	8.903-047.0	Auto Start/Stop Kit 3ph •	8.929-383.0	LanCom Kit 2-step 208/230v 1ph • • •		
8.903-040.0	24" Floor Stand	9.801-033.0	Wall Mount Bracket Assembly	8.903-461.0	Remote On/Off Switch Option • •		
9.801-034.0	36" Floor Stand			8.930-358.0	Additional LanCom Remote		
8.903-617.0	36"Floor Stand (stainless steel)			8.903-619.0	Wall Mount Bracket Assembly		
• Factory Insta	illed * Float Tank cannot be ordered with Wheel Kit	• Not compatib	ole with LanCom	8.930-131.0	Wall Mount Bracket for Fixed LanCom Remote		

• Not available on stainless steel model SEA3-11024D

**DETERGENT FOR EVERY JOB** 

• Not compatible with Auto Start/Stop or Float Tank options

Landa innovative detergent lineup makes your cleaning job easier and faster. Phosphate-free to meet the most stringent environmental demands without sacrificing cleaning effectiveness. We'll match you with a product designed for your specific application.





## Your Authorized Landa Dealer:

8.904-527.0

Wisconsin Steam Cleaner Sales Company 1704 Paramount Court Waukesha, WI 53186 Phone ~ 262-549-9191 email ~ frontdesk@wisteam.com web: www.wisconsinsteam.com

8.903-511.0 Auto Start/Stop Kit 208/230/460v 3ph • •

8.903-448.0 Float Tank Option with Inlet Soap Injection • \* •

Wheel Kit with Detergent Rack (stainless steel)\*

LAN\_SEA © 2021 • 05/21

8.929-380.0 Auto Start/Stop Kit 120v 1ph • • 8.929-381.0 Auto Start/Stop Kit 208/230 1ph • •